



Wuhu R3D Technology Co., Ltd.

Add: Fanchang Economic Development Zone, Wuhu, Anhui,China

Tel: 0086-057488037579

Web: [www.r3dprinter.com](http://www.r3dprinter.com)

Email: [sales@china3dprinter.cn](mailto:sales@china3dprinter.cn)

# Technical Data Sheet

## R3D PLA FILAMENT

Date: 10.11.2021

<b>Dimensions</b>	
Size	1,75 mm
Tolerance	± 0,02 mm
<b>Thermal Features</b>	
Printing Temperature	190-220°C
Platform Temperature	40-60°C
Thermal Deformation Temperature	61.5°C
<b>Physical Features</b>	
Length Per Roll	340M
Density	1.21g/CM <sup>3</sup>
3D printing 100% Filling Tensile Strength	≥35Mpa
Injection Tensile Strength	≥60Mpa
Elongation At Break	4.3-5.8
Melt Flow Rate	6-8g/10min
<b>Packing Features</b>	
Packing Method	Vacuum Sealing + Desiccant
Color Box Size	21*21*6.5CM
Net Weight	1000g
Gross Weight	1350g
<b>Storage</b>	
Cool and dry (15-25°C) and away from direct sun light. This will enhances the shelf life.	